

# Discus™ DRG A125G



**Fast, reliable and easy to set up, Discus™ DRG A125G allows high speed broadband access through a wireless LAN. The device enables both VoIP and data applications.**

Discus™ DRG A125G is a versatile and cost-effective router for reliable and high-speed broadband connectivity.

Subscribers can easily surf the Internet, manage e-mails and communicate in a safe and secure environment. Furthermore, the four Ethernet ports and Wi-Fi 11b/g interface allow the Small/Home Office end-user to extend his private network.

- **ADSL 2/2+**
- **Annex A, B**
- **USB 1.1**
- **4 Ethernet ports 10/100**
- **IP QoS**
- **Wi-Fi 11b/g - Multiple SSID**
- **Security and firewall**

By using a best-in-class and field-proven ADSL2+ chipset platform, DRG A125G delivers the highest level of interoperability with central office equipment, resulting in fast service introduction and no additional qualification costs.

Pirelli can help service providers reduce installation overhead and provide the end user the freedom to manage directly their own network by supplying an optional Smart Setup CD, enabling broadband access in less than 10 minutes.

# Discus™ DRG A125G



## LEDs

Power  
Wi-Fi  
4 Ethernet  
ADSL Link  
Internet  
Usb

## Buttons

1 x Reset Button  
1 x Power Button

## Power Adapter

INPUT: 230Vac 50Hz 135mA  
OUTPUT: 15Vac 0.8 A

## Environmental Specifications

Temperature:  
• Operating: 0 to 40 °C  
• Non Operating: -20 to 65 °C  
Relative Humidity:  
• Operating: 10% to 85% non-condensing  
• Non Operating: 5% to 95% non-condensing

## Agency Approvals and Certifications

CE mark  
ITU-T K21  
Wi-Fi Alliance  
RoHS  
WEEE

## Physical Specifications

Dimensions: 235 x 100 x 185 mm  
Weight: 1.27 kg

## Standard Package Content

DRG A125G  
Power adapter  
Ethernet cable  
USB cable  
Phone cable  
CD  
Safety leaflet

## MAIN FEATURES

<b>WAN interface</b>	1 ADSL Line port (RJ-11 plug) supporting the following standards: <ul style="list-style-type: none"> <li>ADSL (G.992.1, G992.2, T1.413, G994.1, .997.1)</li> <li>ADSL2 (G.992.3)</li> <li>ADSL2+ (G992.5)</li> </ul> Annex A/Annex B are available in different product versions
<b>LAN interface</b>	N° 4 10/100BASE-T Ethernet ports (RJ-45 plug), compliant IEEE 802.3, with auto MDIX and auto-negotiation. Ports can be configured in order to be dedicated to video traffic to/from a STB N° 1 USB Device v 1.1
<b>Wireless Interface</b>	Wi-Fi access point solution is compliant with: <ul style="list-style-type: none"> <li>IEEE 802.11b/g</li> <li>WPA/WPA2 (IEEE 802.11i)</li> <li>WMM (IEEE 802.11e)</li> <li>N°1 external antennas</li> </ul>
<b>ATM features</b>	ATM (AAL5) payload format UBR, VBR-nrt, VBR-rt, CBR traffic classes Up to 8 PVC Pre-emptive SAR Multiple physical queues (up to 8) per traffic class, with priority-based scheduling support*
<b>WAN Protocol Encapsulation</b>	Bridged/Routed Ethernet over ATM (RFC 2684 / RFC 1483) PPP over Ethernet (RFC 2516) PPP over ATM (RFC 2364) IP over ATM (RFC 1577) MTU settable
<b>Routing / Bridging</b>	RIP v1/v2 and static routing NAT/NAPT (with ALGs) IP QoS DHCP Server/Client VPN pass-through IPv4 DNS relay NTP IGMPv2 proxy
<b>QoS</b>	Traffic shaping (ATM layer) Priority-based scheduling (up to 8* queues, max 4 per PVC ) DSCP/TOS remarking
<b>Security</b>	Programmable firewall
<b>Management</b>	DSL Forum TR-069 FTP/TFTP client for remote firmware upgrade Diagnostics and LOGs Telnet with CLI WEB server with Admin/User configuration Pages
<b>VLAN</b>	Supports multiple VLAN ID per ports Configurable layer-two switching



(\*): optional on request