



## 802.11g Wireless Broadband Router w/ 4pt LAN Switch

### ZSR1134WE

### Features:

- Built-in 4 10/100BASE-TX ports with auto MDI/MDIX switch
- Wirelessly Share Internet Connection
- Encryption: WEP / WPA / WPA2
- Provides wireless LAN ACL filtering
- Firewall features NAT with VPN pass-through, MAC, IP, URL Filtering
- Web-based configuration with easy setup wizard for quick installation
- Supports TCP/IP, PPPoE, DHCP, ICMP, NAT



The Zonet ZSR1134WE – **Wireless Broadband Router with 4-port LAN switch** lets you securely share internet connection with wired and wireless computers. Connects as many computers wirelessly as you want and upto 4 wired computers or daisy chain out to switches to expand the network as you need. It offers upto 54Mbps wireless connection and works with your existing Wireless G and Wireless B devices. The advanced firewall featuring NAT w/VPN pass-through, IP/Port/MAC/URL filtering...etc. The Zonet Wireless Broadband Router is the best way to share internet connection, files, printers, and multi-player games with the flexibility and speed!



# 802.11g Wireless Broadband Router w/ 4pt LAN Switch

## ZSR1134WE

### Package content:

- One ZSR1134WE
- One Quick Installation Guide
- One User Manual CD
- One Power Adapter
- One Cradle

### Related Products:

- ZEW1505 11g Wireless Cardbus
- ZEW1605 11g Wireless PCI Aapter
- ZEW2500P 11g Wireless USB Adapter
- ZEW2508 11g Wireless USB Pen-Drive Adapter

### Contact Us:

1.888.883.8880  
[sales@zonetusa.com](mailto:sales@zonetusa.com)  
[www.zonetusa.com](http://www.zonetusa.com)

Zonet USA Corporation  
18513 East Gale Ave. City of Industry, CA 91748  
Tel: 1.626.810.7887 Fax: 1.626.810.8799



## Specification

Standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.3, IEEE 802.3u
Antenna	2dBi Omni-Directional antenna
Wireless Frequency Range	2.412GHz to 2.4835GHz
Wireless Signal Rates (With automatic fallback)	54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 11Mbps, 9Mbps, 6Mbps, 5.5Mbps, 2Mbps, 1Mbps
Wireless Transmit Output Power	54Mbps OFDM : 15dBm $\pm$ 2dBm 11Mbps CCK : 16dBm $\sim$ 18dBm
Modulation	DBPSK, QPSK, CCK and OFDM(BPSK/QPSK/16-QAM/64-QAM)
Wireless Operating Range	Indoors: up to 100 m Outdoors: up to 300 m <i>* Environmental factors may adversely affect operating range</i>
Security	Hardware-Based Encryption/Decryption using 64/128-bit WEP keys and also support WPA/WPA2
Firewall Features	NAT (Network Address Translation) with VPN pass-through MAC and IP address filtering URL filtering
LED Indicators	Power/Link/Activity, WAN, LAN,
Dimension(L x W x H)	156 x 102 x 31 mm or 6.1 x 4.0 x 1.1 In.
Temperature	Operating: 0 °C $\sim$ 50 °C Storage: -20 °C $\sim$ 70 °C
Humidity	Operating: 5% $\sim$ 90% non-condensing Storage: 5% $\sim$ 90% non-condensing
Certifications	FCC, CE

\*Maximum wireless signal rate derived from IEEE 802.11b/g specifications. Actual data throughput will vary from volume of network traffic, building materials and construction, and network overhead, lower actual data throughput rate.

Zonet is a registered trademark. Other Brands and product names are trademarks of their respective holders. Information provided in this document pertains to Zonet products and is subject to change at any time, without notice. For the most recent product information please visit <http://www.zonetusa.com>

Copyright © Zonet. All Rights Reserved.